


EPTFE-Series Electronics Grade PTFE

EPTFE-Series High Purity Electronics Grade PTFE Filter Cartridges, with expanded polytetrafluoroethylene (PTFE) membrane, provide superior chemical resistance in high-purity microelectronics applications. With retention ratings as fine as fine as 0.01 micron (10 nanometers), consistent contaminant removal is achieved in aggressive fluids and organic solvents. In air and gas applications, the single-layer PTFE membrane delivers superior hydrophobicity versus polypropylene or PVDF, offering a superior option to preclude water wetting and associated diminished flow. Each element is integrity tested to assure optimal performance. Manufactured in a clean-room environment to maintain high standards of purity and cleanliness.



Flow Rate vs Pressure Drop



Typical Applications

- Solvent Filtration
- Etching Bath Solutions
- High Purity Rinse Water
- Photochemical Solutions
- Bulk Chemical Delivery
- Ultrapure Electronics-Grade Gases

Construction Materials

Membrane	PTFE
Support Media	Polypropylene
End Caps	Polypropylene
Center Core	Polypropylene
Outer Support Cage	Polypropylene
O-Rings/Gaskets	Buna, EPDM, Silicone Teflon® Encapsulated Viton® ¹ , Viton®

Note: Cartridges are available with wet-pack option (60/40 IPA/DI water solution) to eliminate the need to wet-out in the environment.

Dimension (Nominal)

Length	10 to 40 in (25.4 to 101.6 cm)
Outside Diameter	2.7 in (7.0 cm)

Operating Conditions

Change Out ΔP (recommended)	35 PSID (2.4 bar)
Temperature (max)	176°F (80°C)
Differential Pressure (max)	50 PSID at 68°F (3.4 bar at 20°C)

Food Safety Compliance

Materials of construction comply with FDA regulations for food and beverage contact use as detailed in the US Code of Federal Regulations, 21CFR. Materials used to produce filter media and hardware are deemed safe for use in contact with foodstuffs in accordance with EU Directives 1935/2004, and/or 10/2011.

Ordering Information

EPTFE	Rating(µ)	A	Length	C	End Cap Style	O-Rings/Gaskets	-	Options
	0.01 (10 nm)		10" (25.4cm)		2 = DOE Flat Gasket ¹	B = Buna		I = Stainless Steel Insert
	0.02 (20 nm)		20" (50.8 cm)		3 = 222 w/Fin	E = EPDM		W = Wet-Packed
	0.03 (30 nm)		30" (76.2 cm)		4 = 222 w/Flat Cap	S = Silicone		
	0.05 (50 nm)		40" (101.6 cm)		6 = 226 w/Flat Cap	T = Teflon® Encapsulated Viton® ¹		
	0.1				7 = 226 w/Fin	V = Viton®		
	0.2				28 = 222 3-Tabs w/ Fin			
	0.45							

1 - When ordering with DOE Flat Gasket, gasket style "T" is not available
 2 - When ordering with DOE Flat Gasket, gasket style "Z" is not available

DISCLAIMER: Filtration data presented is representative of performance observed in controlled laboratory testing. It is not given as a warranty, specification or statement of fitness for use. Specific performance can vary widely depending on contaminant type, fluid properties, flow rates and environmental conditions. It is recommended that users conduct thorough qualification testing to assure the product functions as required. For additional technical support, a product Performance Guide is available upon request.